# TECHNICAL FEATURES BADGY100 & BADGY200

# badgy A LASTING IMPRESSION

### GENERAL FEATURES

- Single-side print module
- Color sublimation, monochrome thermal transfer
- Printing resolution: 260 x 300 dpi
- 2 million colors
- 16 MB of memory (RAM)
- Printable area:
  - BADGY100: margin of 1.35 mm
  - BADGY200: edge-to-edge

#### PRINTING SPEED

- Color (YMCKO):
  - BADGY100: 45 s/card 80 cards/h
  - BADGY200: 38 s/card 95 cards/h
- Black:
  - BADGY100: 16 s/card 225 cards/h
  - BADGY200: 11 s/card 325 cards/h

#### PORTS/CONNECTIVITY

USB 2.0 (USB 1.1 and 3.0 compatible)

#### SECURITY

Space for Kensington<sup>®</sup> security lock

## ECO-DESIGN, CERTIFICATIONS AND DECLARATION OF CONFORMITY

- Extended standby mode and reduced electricity consumption
- CE, CCC, KCC, VCCI, FCC, ICES, BIS, EAC
   RoHS

#### POWER SUPPLY

- Power supply unit:
- 100-240 V AC, 50-60 Hz, 1.7 A
- Printer: 24 Volts DC, 2.71 A

#### DIMENSIONS AND WEIGHT

- Complete packaged solution:
   Dimensions (H x W x D): 315 x 385 x 285 mm
  - (12.4" x 15.15" x 11.22") • Weight: 3.95 kg (8.7 lbs)
- Printer:
- Dimensions (H x W x D): 148 x 200 x 276 mm (5.83" x 7.87" x 10.86")
- Weight: 1.665 kg (3.67 lbs)

#### MANAGEMENT AND CARD FEATURES

- Card feeder capacity: 25 cards (0.76 mm) to 40 cards (0.50 mm)
- Output hopper capacity: 25 cards (0.76 mm) to 40 cards (0.50 mm)
- Card thickness: 0.50 to 0.76 mm, automatic adjustment of the gauge
- Card type: PVC cards and paper cards
- Card format: ISO CR-80 ISO 7810 (53.98 x 85.60 mm)

#### PRINTING RIBBONS

- Available to order:
  - YMCKO: 100 prints/ribbon
  - Monochrome black ribbon: 500 prints/ribbon (integrated ribbon saving)
- BlackFlex monochrome ribbon, dedicated to the use with paper cards
   500 priote (integrated gibbar second)
- 500 prints (integrated ribbon saver)

  Automatic recognition and configuration
- Ribbon inserted in a cassette for easier handling

#### **OPERATING ENVIRONMENT**

- Min/max operating temperature: 15° / 30° C (59° / 86° F)
- Humidity: 20% to 65% non-condensing
- Min/max storage temperature: -5° / +70° C (23° / 158° F)
- Storage humidity: 20% to 70% non-condensing
- Ventilation in operation: free air circulation

### SOFTWARE

- Delivered with Evolis Badge Studio<sup>®</sup> for badge design and editing (via a download link):
  - **BADGY100:** Evolis Badge Studio®
  - BADGY200: Evolis Badge Studio® Plus with file import from databases and vCard module.
  - Compatible with Windows® and macOS®
- Delivered with Badgy Premium Suite<sup>®</sup> for Windows<sup>®</sup> and macOS<sup>®</sup>:
  - Printer driver (Windows certification)
  - Printer management and configuration tool with graphic notifications
- User interface languages available: Arabic, Chinese (Simplified), Chinese (Traditional), Czech, Danish, Dutch, English, Finnish, French, German, Hungarian, Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish.
- Detailed driver compatibility available on www.badgy.com

#### PACKAGE CONTENTS

#### BADGY100:

- BADGY100 printer
- Color ribbon (YMCKO) 50 prints
- 50 blank PVC cards 0.76 mm (30 mil)
- Download link for the Evolis Badge Studio® software
- Power supply unit and cable
- USB cable

#### BADGY200:

- BADGY200 printer
- Color ribbon (YMCKO) 100 prints
- 100 blank PVC cards 0.76 mm (30 mil)
- Download link for the Evolis Badge Studio® Plus software
- Power supply unit and cable
- USB cable

#### WARRANTY CONDITIONS<sup>1</sup>

- 2 years (printer and print head)
- Warranty extensions available as an option

1 Warranty subject to strict compliance with the specific usage conditions and the use of Badgy print ribbons. The costs of return remain the responsibility of customer.

